






REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
V1.0	DWG.REL	2023.8.19	ZZM	JIN



- Material
 - ØHousing : PA66,UL94V-0
 - ØScrew : M3.0 Steel, Zinc plated
 - ØTerminal : Copper alloy, Tin plated
- Electrical
 - UL IEC
 - Rated voltage : 300V 250V
 - Rated current : 15A 24A
 - Contact resistance : 20mΩ(Max)
 - Insulation resistance: 500MΩ/DC500V
 - Withstanding Voltage : AC2000V/1min
 - Wire range: 22-14AWG;2.5mm²
- Mechanical
 - Operating temperature:-40℃~+105℃
 - Soldering temperature:250℃±5/5sec
 - Torque: 0.8N.m (7.02Lb.in)
- Conform to REACH and RoHS

HOW TO ORDER
 2KF024-7.62-XXP-1 X-XXXX

MODEL Pitch:mm
 No. of poles: 2P

Color:
 G:Green R:Red
 K:Black W:White
 O:Orange B:Blue
 GR:Gray

1:Single Pitch
 2:Double Pitch

Customer Request

Pitch range	Nominal dimension range	PROJECTION	UNIT	TITLE
>0 ~6	>6 ~10	0.1/10	mm	2KF024-7.62-2P-1K-001A
±0.15 ±0.20	±0.30 ±0.30	±2°	SHEET SIZE	A4 SERIES 2KF024
DRAWING TYPE		CUSTOMER DRAWING		
SCALE		1:1 SHEET 1 OF 1		
DRAWING NO.		W12005452		

DF 慈溪市凯峰电子有限公司
 CIXI KAIFENG ELECTRONICS CO.,LTD